Single-Phase Transformer Characteristics

PRODUCT FEATURES | TECHNICAL SPECIFICATIONS | APPLICATION GUIDANCE

01 Product Overview

A single-phase transformer operates with single-phase AC at both its input and output. Its simple structure, compact size, and low cost suit single-phase loads, galvanic isolation, and voltage conversion. This guide focuses on residential, rural, and small-commercial applications in Africa and Southeast Asia, subject to local utility requirements.

02 Operating Principle

Operation is based on electromagnetic induction ($U_1/U_2 \approx N_1/N_2$). Alternating magnetic flux is established in the single-phase core, with primary and secondary windings mounted around the core limbs. Designs include core-type (EI) and shell-type constructions. Toroidal cores provide higher efficiency and lower leakage flux.

03 Main Structure and Components

Core. Laminated silicon-steel construction (EI/core type or shell type), or a wound toroidal core.

Windings. Primary and secondary windings made of copper wire (aluminum optional), with interlayer insulation.

Insulation and varnish impregnation. Smaller units commonly use dry-type air/resin insulation; larger-capacity units may be oil-immersed.

Enclosure and mounting. Open-frame or enclosed versions; distribution configurations include pole-mounted, underground, and box-type installations.

Terminals and protection. Connection terminals, optional fuses, and optional temperature control.

04 Product Classification

Application. Isolation, step-down/step-up, control, lighting, signal, and pole-mounted single-phase distribution transformers.

Core design. Core-type (EI), shell-type, or toroidal.

Insulation medium. Dry-type (smaller units) or oil-immersed (distribution units).

Installation. Pole-mounted, floor-mounted, or underground.

05 Key Technical Specifications (Typical Values)

ITEM	TYPICAL SPECIFICATION
Rated capacity	Small units: several VA to tens of kVA; distribution ratings per utility specification.
Rated voltage	Utility-specified primary; LV: 220 / 230 / 240 V, depending on country and network.
Rated frequency	50 Hz in most target markets; 60 Hz where required (e.g., Philippines).
Connections	Primary and secondary connections, neutral, and earthing to utility requirements; do not assume a center-tapped secondary.
Insulation class	Dry-type: Class B/F/H; oil-immersed: Class A.
Temperature-rise limits	Dry-type: according to insulation class; oil-immersed winding: ≤65 K.
Efficiency	Small units: typically ≥90%; distribution-class: typically ≥98%.
Applicable standards	IEC 60076 / IEC 61558 as applicable; local utility and national requirements.

06 Product Features and Advantages

Simple construction. Fewer components and relatively low manufacturing costs.

Compact and lightweight. Convenient installation and transportation, particularly for pole-mounted types.

High efficiency. Distribution-class single-phase transformers can exceed 98% efficiency.

Flexible configurations. Three single-phase units can form a three-phase transformer bank, facilitating spare-unit arrangements.

Single-phase load compatibility. Suitable for residential, lighting, signaling, and control-circuit loads.

Considerations. For higher-capacity applications, three-phase transformers are generally preferable because they use less material and offer higher efficiency. Large single-phase transformers can be bulky, heavy, and costly.

07 Applications and Industries

Residential distribution. Single-phase supplies for homes, village shops, schools, and clinics in Africa and Southeast Asia, using utility-approved voltage and connection arrangements.

Transport and communications. Railway signaling, telecommunications power supplies, and street lighting.

Controls and instrumentation. Control circuits, instrument supplies, and electrical isolation.

Voltage conversion. Match equipment to the actual local supply voltage; confirm the required ratio.

Rural and off-grid supply. Village electrification, farm loads, and mini-grids with compatible AC supplies.

08 Selection Guidelines

Capacity. Calculate according to single-phase load demand and coincidence factor.

Voltage ratio. Confirm utility primary and LV voltages, connection, neutral, and earthing.

Frequency. Confirm local supply: commonly 50 Hz; 60 Hz where required, including the Philippines.

Mounting arrangement. Pole-mounted, floor-mounted, or underground.

Insulation and protection. Specify site temperature, humidity, altitude, dust, and coastal corrosion protection.

Standards. Specify applicable IEC parts, national rules, and the local utility specification.

09 Frequently Asked Questions and Standard Responses

Q1. Where are single-phase transformers used?

Answer. For homes, village shops, farms, lighting, telecoms, and control circuits in Africa and Southeast Asia; also for voltage conversion and galvanic isolation, with ratings matched to the local network.

Q2. Which voltages suit Africa and Southeast Asia?

Answer. Confirm the country and utility. LV examples include 230 V in Malaysia and 240 V in Kenya; primary voltage, connection, neutral, and earthing must match the actual network.

Q3. How do I choose between single-phase and three-phase?

Answer. For three-phase loads and larger ratings choose three-phase; for single-phase loads, small ratings or special installations choose single-phase. Three single-phase units can form a three-phase bank.

Q4. Is 60 Hz supported?

Answer. Yes. Specify 50 Hz or 60 Hz for the utility (e.g., 60 Hz in the Philippines); verify the nameplate.

Q5. Can you supply isolation transformers?

Answer. Yes. 1:1 isolation and safety low-voltage designs are available on request.

Q6. Do you supply pole-mounted single-phase transformers?

Answer. Yes. Specify kVA, voltages, frequency, mounting, and the destination utility's requirements.

Q7. What is the efficiency?

Answer. Distribution-class single-phase transformers typically achieve ≥98% efficiency; smaller units are slightly lower.

Q8. Warranty and service life?

Answer. Warranty is 12 months from shipment under agreed terms. Design life is over 20 years.

10 Related Standards and Certifications

IEC 60076 series for power/distribution transformers; applicable IEC 61558 parts for small isolation/control transformers. Confirm destination-country regulations, national adoptions, utility specifications, and required tests/approvals per project. Compliance or certification is subject to verified documentation.